



PCB Layout
(PCB TOLERANCE ± 0.05)

Shinning P/N	HUAWEI P/N
1265-032-48-3	14200242

Performance characteristics:

1.Main body part material

Insulator: LCP Black UL94V-0

Contact terminal: Phosphor bronze, 1.27μm Ni under plating,

Contact area plating Au 0.76μm,Tail plating matte Sn 3-5μm

2.Electrical requirements

Current rating: 3 A

Contact resistance: ≤20mΩ

Insulation resistance: ≥5000MΩ

Withstanding voltage: 1000 Vr.m.s, 1mA, 60s

Durability:100 Cycles

3.Mechanical requirements

Insertion force: ≤1.8 N/Pin

Extraction force: ≥0.3 N/Pin

4.Environment specification

Working temperature: -55℃~+125℃

Resistance to soldering heat: 260℃, 30s

(Re-flow profile for soldering)

5.Packing & storing

Method of packing: Tape&reel, outer box

Storing condition: temperature of -10℃~+40℃
below 80% relative humidity

6.Style of installation: SMT

7.To prevent the pollution of the environment product info

Rohs agreement:in line with the european union rohs.

1265 - 03 2 - 4 8 - 3					
Series No.	Terminal number per row 03		Spec code Code Definition 2 A B 8.50 6.70		Plating code Code Definition 8 Au 0.76μm Sn
			Spec code Code Definition 4 Double Row With peg		Insulator material & color Code Definition 3 LCP BLACK UL94V-0

Unless otherwise specified tolerance:

X.	±0.50	X.°	±3°
.X	±0.38	.X°	±2°
.XX	±0.25		

①	2	SN-00003409	Tim Lv	2014.02.21
Mark	NO.	File NO.	Signature	Date
DRAW			Tim Lv 2013.11.09	
CHK				
MAN				
STD				
APP				

2.54mm receptacle double row
SMT socket 2*3Pin
(Customer:HUAWEI)

1265-032-48-3

SL0.1265.002

Projection	Rev.	Weight	Scale
	A1		
All Dimensions in mm		Sheet 1 of 1	
 SHINNING SHENZHEN SHINNING ELECTRONIC CO.,LTD.			